

# INFORMATION & DIRECTIONS FOR USE

*Sécurité*  
**COUPE**  
**10.52**



Cut resistant seamless glove gauge 10 knitted in cut-resistant technical fibers for use in a fatty, aqueous and acidic food environment.

Knitted in full with the same thread, without fiberglass, it guarantees optimal protection against risks of cuts.

Ambidextrous and delivered pre-washed, it offers great dexterity.

This glove meets the requirements of the regulation (UE) N° 2016/425.

## Description



EN 388 : 2016

Gauge	10
Color	blue & white
Cuff	10 cm
Size	6 to 11
Weight	35gr approx.

Abrasion resistance	4
Cut resistance coupe test	5
Tear resistance	4
Puncture resistance	1
Cut resistance TDM	F
EN ISO 13997 is 43,0N (Newton)	

## Mark



## Suitable for food contact



## EN 420+A1 : General requirements

Performance levels are obtained by tests done in environmental conditions precisely defined by the norms. Therefore, any use in new conditions is the responsibility of the user.

**DIRECTION FOR USE :** Protective and handling glove for fatty, aqueous, acidic food environments with strong cut protection.

This glove is resistant to traction and should not be used when there is a risk of being caught by moving machines.

## CATEGORY II PERSONAL PROTECTIVE EQUIPMENT

**MAINTENANCE INSTRUCTIONS :** Store away from light and moisture, preferably between 5°C and 25°C, in ventilated rooms.

Wash at 85°C, dry at 50°C.

Regeneration under the responsibility of the user. We do not guarantee the performance levels of regenerated products.